

MONARFLEX Scaffband Stripe

Technical Data Sheet

Features

MONARFLEX Scaffband Stripe has a strong 9x12 reinforcement grid in 1670 dtex Polyester yarn protected by 2 layers of Low Density Polyethylene (LDPE) with UV stabilisation. With the use of these components, the product is thinner, lighter and yet stronger than other competitive products.

Durability

We recommend MONARFLEX Scaffband Stripe for all types of projects of 6 - 12 months duration. The combination of high quality components form a tough and durable sheeting for rough working conditions including sandblasting and water jetting.

Application

MONARFLEX Scaffband Stripe is designed to be applied both vertically and horizontally. The fixing bands form a system that suits most standard scaffolding systems. Fixing the sheeting to the scaffold must be done according to calculations taking factors like wind and height of the surrounding buildings into consideration. We recommend the use of 1 fixing/m² but any fixing must be placed according to calculations for each project.

Available Sizes	Roll Weight
2.00m x 45m	17 kg
2.25m x 40m	17 kg
4.00m x 36m	28 kg
Gross Weight	210 g/m ²
Thickness	0.15 mm
Tensile Strength	MD >10 kN/m TD >12kN/m
Eyelet Pull-out Strength	550 N at 100mm centres on reinforced bands, positioned horizontally along the length of the sheet
Tear Strength	225 N
Light Transmission	80%
Test Methods	Conforms to EN12310-2, EN12311-2
Material	Reinforced Low Density Polyethylene
Colour	Clear

